











Wide Range to Suit Different Pump Delivery Heads

Technical Details	Pipe Size		(1")	(1¼")	(1½")	(2")	(2½")	(3")	(4")	(5")	(6")
			OD: 33mm ND: 25mm	OD: 42mm ND: 32mm	OD: 48mm ND: 40mm	OD: 60mm ND: 50mm	OD: 75mm ND: 65mm	OD: 88mm ND: 80mm	OD: 113mm ND: 100mm	OD: 140mm ND: 125mm	OD: 165mm ND: 150mm
Safe Total Pump Delivery Head (m)	V4 - 12.5		125	125	125	-	-	-	-	-	-
	V4 - 15		150	150	150	-	-	-	-	-	-
	Medium		-	-	-	130	100	110	100	-	-
	Crystal		210	210	210	170	-	-	-	-	-
	Standard		300	250	260	200	160	170	150	160	-
	Standard Plus		-	-	-	-	210	210	210	210	-
	Heavy		-	350	350	270	260	260	260	260	260
	Super Heavy		-	400	400	350	350	350	350	350	-

Technical Details	Pipe Size		(1")	(1¼")	(1½")	(2")	(2½")	(3")	(4")	(5")	(6")
			OD: 33mm ND: 25mm	OD: 42mm ND: 32mm	OD: 48mm ND: 40mm	OD: 60mm ND: 50mm	OD: 75mm ND: 65mm	OD: 88mm ND: 80mm	OD: 113mm ND: 100mm	OD: 140mm ND: 125mm	OD: 165mm ND: 150mm
Safe Pulling Load with Chain Pulley (kgf)	V4 - 12.5		480	770	1000	-	-	-	-	-	-
	V4 - 15		600	1000	1200	-	-	-	-	-	-
	Medium		-	-	-	1450	1800	2600	4000	-	-
	Crystal		750	1100	1500	1850	-	-	-	-	-
	Standard		1100	1500	1700	2100	2700	4000	5900	9650	-
	Standard Plus		-	-	-	-	3500	4850	7650	12250	-
	Heavy		-	1800	2400	2800	4200	5650	9350	14600	23500
	Super Heavy		-	1850	2400	3350	5300	7300	12150	18600	-